Approved ASSReiss 2002/91/93: CIA-RDP80-00810A003500880009-8

CENTRAL INTELLIGENCE AGENCY

REPORT NO.

INFORMATION REPORT CO NO. THE CASE A CASE BY LEVEL TO SEE

COUNTRY

East Germany

DATE DISTR. 17 February 1954

1

SUBJECT 4

Development of the LD-12 Tube at the HF Plant NO. OF PAGES

PLACE ACQUIRED

DATE OF INFO.

NO. OF ENCLS. CLISTED BELOW 25X1A

SUPPLEMENT TO REPORT NO.

TRIS DOCUMENT CONTAINS INFORMATION AFFECTING THE TRATIONAL DEFRINGS OF THE UNITED STATES, WITHIN THE BEANING OF TITLE 16, SECTIONS 75 APP. 784. OF YIEL 9. COOPER. 54 AURISIDED. ITS PRANSHISTION OR REVEL-ATION OF ITS CONTENTS TO GO RECEIFF OR AS UNANTROSTEE PERSON OF FORMETTE SPEAKY USE REPRODUCTION OF THIS FORM IS FORMETTE. 

THIS IS UNEVALUATED INFORMATION

25X1X

The Work fuer Fernmeldewesen HF, Berlin-Oberschoeneweide, has resumed the development of the LD-12, an indirectly heated triode used in decimeter wave technology. During World War II this tube had been manufactured for the German Wehrmacht. Its new development in the HF plant is completed, and it is to go and into production in 1954.

The LD-12 is a tube for the eight-centimeter range with a power of 10 watts. The following is additional data:

Hesting voltage: 12.6 Wolts (A.C.)

Heating current: 0.8 amperes

Anode voltage: 400 Volts

Anode current: 15 :1111-emperes

Grid voltage: minus 2.5 Volts

Conductance: 9 mA/V

Internal resistance: 0.01 nega Ohms

25X1A

STATE	X.	HAVY	20	NSRB	DISTRIBUTION	ORR	Ev	X	OSI	Ev	
ARMY	/X	AIR	Vi X	FBI		1		1			